

Submittal Data Information KS Kickspace Series

Effective: January 12, 2018

Q	UI	E7	- 0	NE	20	00	0	\equiv
---	----	----	------------	----	----	----	---	----------

Job: E	ngineer:	Contractor:	Rep:
ITEM NO.	MODEL NO.		

ENGINEERING SPECIFICATIONS

Construction

- ·One piece chassis with removable grille
- ·Made of galvanized steel
- ·Stainless steel grille

Heat Exchanger

- ·Headered coil
- ·Copper tubes expanded into aluminum plate fins
- ·Tested at 300psi

Fan & Motor Assembly

- ·High static fan wheel and scroll
- ·Detachable motor
- ·Replaceable "easy glide" sleeve bearings
- ·Fan and motor cut out protected to UL/CSA specs

Controls

- ·2-Speed (max-on-off) fan switches
- ·Low limit aquastat will close on rise to 105°F and open at 88°F


Water Connections

- •S&R connections are 1/2" sweat on the right of unit
- ·Water vent easily accessible through grille

Electrical Connections

·120/60/1 power supply required

DIMENSIONS								
Model #	Α	В	С	D	Wt (lbs)			
KS 2004	10 7/8"	13 7/8"	13 7/8"	3 1/2"	9			
KS 2006	10 7/8"	13 7/8"	20"	3 13/16"	10			
KS 2008	10 7/8"	13 7/8"	20"	3 13/16"	10			
KS 2010	14 13/32"	17 23/32"	23 5/8"	4"	14			



	Capacities for Quiet-One 2000 Kickspace Heaters - BTU/hr @ 65°F Entering Air										
	Flow Rate	Pressure Drop (ft)	4000				ees F) - BTU/hrs.		1000		-1-0
Unit G	GPM		130°	140°	150°	160°	170°	180°	190°	200°	210°
	1	0.06	2095	2410	2700	3000	3350	3650	3860	4000	4105
KS 2004	3	0.422	2240	2650	3000	3350	3765	4120	4350	4530	4635
	5	1.026	2350	2755	3140	3530	3940	4330	4590	4810	4935
	1	0.12	3410	4050	4655	5265	5860	6330	6700	7110	7270
KS 2006	3	1.19	3735	4395	5060	5735	6330	6825	7120	7530	7790
	5	2.6	3860	4540	5225	5910	6560	7030	7415	7800	8010
	1	0.12	4300	5000	5765	6500	7370	7960	8400	8735	8920
KS 2008	3	1.19	4580	5380	6195	7050	7930	8610	9010	9445	9740
	5	2.6	4760	5625	6450	7290	8200	8925	9360	9785	10020
	1	0.41	5530	6350	7150	7975	8780	9465	9975	10330	10520
KS 2010	3	2.78	5880	6710	7740	8710	9625	10540	11060	11530	11740
	5	3.92	6070	7030	8000	9030	10025	10920	11525	11995	12180

 $^{^{\}sim}$ For low speed ratings: .85 KS 2004; .75 KS 2006; .70 KS 2008; and .65 KS 2010.

As part of our continuous product improvement, Smith's Environmental Products reserves the right to alter specifications without notice.



[~] Heat throw: 10' @ 50 cfm KS 2004; 10' @ 75 cfm KS 2006; 10' @ 90 cfm KS 2008; 10' @ 125 cfm KS 2010.